



BC285.5 BRUSH SHREDDER FOR SKID LOADERS



- Universal skid loader hitch
- Fits most skid loaders with high flow hydraulics (requires 35-55 GPM at minimum of 3000 psi)
- Reduces trees and brush up to 6 inches in diameter to mulch
- Reduces tire punctures, leaves smooth stumps, not sharp stobs

- Adjustable multi-position skid shoes allow adjustable cut height
- Reduces liability from flying debris
- Discharges material down and under the machine with minimal unidirectional front discharge
- SAE standard parts, not metric



Tip to tip cutting diameter of the rotor is 28 inches (711 mm). The rotor is fitted with carbide tip heat treated steel cutters which are quick change, pocket mounted incorporating cutter overlap.

- Three optional hydraulic motor sizes allows custom fitting to the skid loader hydraulic.
- Fixed tooth rotor with carbide tipped steel quick change teeth
- Final drive through a cog belt drive
- Dynamically balanced rotors
- Greasable rotor bearings

Specifications

Gear type hydraulic motor - Optionally 3.8 or 5.4 cubic inch displacement, pressure limited to 3000 psi, or 4.14 at 4500 psi

Final drive - Cog belt and sprockets

Working diameter - 28" (711 mm)

Cut width - 67"

Overall unit width - 77"

Number of cutters - 54

Weight - 3400 lbs.

Recommended Skid Steer Options:

- Cab enclosure with A/C
- Lexan cab glass
- Foam filled tires