



## PTOBC285.5 BRUSH SHREDDER FOR TRACTORS WITH 1000 RPM PTO DRIVE



- Universal 3 point hitch CAT II or III
- Fits most tractors 85-160 PTO HP with 1000 RPM, 1 3/8 – 21 spline PTO shaft
- Reduces trees and brush up to 10 inches in diameter to mulch
- Reduces tire punctures, leaves smooth stumps, not sharp stobs

- Adjustable multi-position skid shoes allow adjustable cut height
- Reduces liability from flying debris
- Discharges material down and under the machine with minimal unidirectional front discharge
- SAE standard parts, not metric



### Specifications

**Right angle gear box with slip clutch and overrunning load clutch**

**Final drive - Cog belt and sprockets**

**Working diameter - 28" (711 mm)**

**Cut width - 67"**

**Overall unit width - 77"**

**Number of cutters - 54**

**Weight - 3900 lbs.**

Tip to tip cutting diameter of the rotor is 28 inches (711 mm). The rotor is fitted with carbide tip heat treated steel cutters which are quick change, pocket mounted incorporating cutter overlap.

- Fixed tooth rotor with carbide tipped steel quick change teeth
- Final drive through a cog belt drive
- Dynamically balanced rotors
- Greasable rotor bearings

### Recommended Tractor Options:

- Cab enclosure with A/C
- Lexan cab glass
- Logger or foam filled tires
- Hydrostatic creeper or infinitely variable transmission